

# BlueTronic II 10W-40

Passenger car engine oil



## Description

The engine oil with Aral Synth Technology provides good anti-wear capabilities and keeps engines clean. For gasoline and diesel engines.

## Typical Characteristics

Name	Method	Units	ral BlueTronic II 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.864
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.3
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	95
Viscosity Index	ASTM D2270	None	152
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6300
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% w t	1.2

## Product Performance Claims

ACEA A3/B4

API SP

VW 501 01/ 505 00

Meets - Fiat 9.55535-D2

Fulfills the technical requirements of MB 229.3

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BlueTronic II 10W-40

08 Jan 2025

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence. This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Air BP Lubricants/BP Lubricants USA Inc., 1500 Valley Road , Wayne , NJ 07470, USA

+1 973 633 2200

[www.airbp.com/lubricants](http://www.airbp.com/lubricants)

